



Material	Stone Mosaic & Waterjet
Finish	Honed
Thickness	3/8"
Cut and Fill Size	12-1/2" x 12-1/2"
Square Feet/Piece	1.0333
Mounting	Mesh
Available Colors White	

Usage	
	Commercial Interior Floor & Wall
	Commercial & Residential Exterior Wall
	Residential Interior Floor & Wall
	Shower Floor
	Shower Wall
	Steam Shower

Material Data	
	Color Variation
Sealing	
	Sealing required prior to grouting
Cleaning and Maintenance	
	Protect from harsh abrasive cleaners and tools <i>Recommended: Oceancare or Dry Treat products</i>

Notes:

- We recommend sealing all Natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a Natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- Shower floor installations require special procedures.
- If used for shower floors, must include waterproof membrane on substrate and 12 inches up adjacent walls prior to tile installation.
- White thin-set or mortar is required (limestones, tumbled stones, "antiqued stones", and light colored marbles)
- May be characterized by dry seams, pits, fossils, and glass veins (honed stones are often filled at the factory)

