



Material	Stone Mosaic
Finish	Textured
Thickness	3/8"
Cut and Fill Size	11 4/5" x 11 4/5"
Square Feet/Piece	0.968
Mounting	Mesh
Available Colors Charcoal Grey/White	

Usage	
(7)	Bathroom Floor
	Commercial Interior & Exterior Floor & Wall
(7)	Residential Bathroom Floor
	Residential Interior & Exterior Floor & Wall
	Shower Wall
	Steam Shower Wall

Material Data		
MEDIUM	Color Variation	
Sealing		
	Sealing required prior to grouting	
Cleaning and Maintenance		
Es.	Protect from harsh abrasive cleaners and tool Recommended: Oceancare or Dry Treat products	

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles.

 Likely identified with dry seams, pits, fossils and glass veins that are
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

