


## SHIFT Chevron Mosaic



Material	Stone Mosaic	
Finish	Textured	
Thickness	3/8"	
Cut and Fill Size	7 3/5" x 8 1/5"	
Square Feet/Piece	0.4363	
Mounting	Mesh	
Available Colors Charcoal Cream Grey White		

Usage	
(7)	Bathroom Floor
	Commercial Interior & Exterior Floor & Wall
(7)	Residential Bathroom Floor
	Residential Interior & Exterior Floor & Wall
	Shower Wall
	Steam Shower Wall

Material Data		Charcoal	Cream	Grey	White	
MEDIUM	Color Variation	<b>~</b>	<b>~</b>	<b>✓</b>		
HIGH	Color Variation				<b>✓</b>	
Sealing						
	Sealing required prior to grouting					
Cleaning and Maintenance						
Protect from harsh abrasive cleaners and tool Recommended: Oceancare or Dry Treat products						

## Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles.
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

