



<b>Material</b>	Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	10 3/8" x 9 1/8"
<b>Square Feet/Piece</b>	0.6623
<b>Mounting</b>	Mesh
<b>Available Colors</b>	
Calacata (Calacata)	
Crema (Crema Vecchia, Lagos Gold)	

Usage	Calacata	Crema
Commercial Interior Floor	✓	
Commercial Interior & Exterior Wall	✓	interior only
Residential Bathroom Floor	✓	✓
Residential Interior Floor	✓	✓
Residential Interior & Exterior Wall	✓	interior only
Shower Floor	✓	
Shower Wall	✓	✓
Steam Showers		wall only

Material Data	Calacata	Crema
<b>MEDIUM</b> Color Variation		✓
<b>HIGH</b> Color Variation	✓	
<b>Sealing</b>		
Must be sealed for use in areas that experience frequent wet conditions	✓	✓
<b>Cleaning and Maintenance</b>		
Protect from harsh abrasive cleaners and tools <i>Recommended: Oceanscare or Dry Treat products</i>		

**Notes:**

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

