



Material	Stone
Finish	Honed
Thickness	3/8"
Cut and Fill Size	11 1/2" x 11 13/16"
Square Feet/Piece	0.9434
Mounting	Mesh
Available Colors	
Ash	
Crema	
Calacata	

Usage		Ash	Calacata	Crema
	Commercial Interior Floor		✓	
	Commercial Interior & Exterior Wall	interior only	✓	interior only
	Residential Bathroom Floor	✓	✓	✓
	Residential Interior Floor	✓	✓	✓
	Residential Interior & Exterior Wall	interior only	✓	interior only
	Shower Floor		✓	✓
	Shower Wall		✓	✓
	Steam Showers		wall only	

Material Data		Ash	Calacata	Crema
	Color Variation	✓		✓
	Color Variation		✓	
Sealing				
	Must be sealed for use in areas that experience frequent wet conditions	✓	✓	✓
Cleaning and Maintenance				
	Protect from harsh abrasive cleaners and tools Recommended: Oceanscare or Dry Treat products			

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

