













Material	Stone
Finish	Honed
Thickness	3/8"
Cut and Fill Size	8" x 15 1/4"
Square Feet/Piece	0.8475
Mounting	Mesh
Available Colors	
Ash (Ash, Calacata, Flannel)	
Calacata (Calacata)	

Usage		Ash	Calacata
	Commercial Interior Floor		✓
	Commercial Wall Interior & Exterior	interior only	✓
	Residential Bathroom Floor	✓	✓
	Residential Interior Floor	✓	✓
	Residential Wall Interior & Exterior	interior only	✓
	Shower Floor		✓
	Shower Wall		✓
	Steam Showers		wall only

Material Data		Ash	Calacata
MEDIUM 	Color Variation	✓	
HIGH 	Color Variation		✓
Sealing			
	Must be sealed for use in areas that experience frequent wet conditions	✓	✓
Cleaning and Maintenance			
	Protect from harsh abrasive cleaners and tools <i>Recommended: Oceanscare or Dry Treat products</i>		

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

