



<b>Material</b>	Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	9 5/8" x 10 1/2"
<b>Square Feet/Piece</b>	0.8130
<b>Mounting</b>	Mesh
<b>Available Colors</b>	
Calacata (Calacata)	
Celeste (Ash, Calacata, Celeste)	
Crema (Crema, Lagos Gold, Linen)	

Usage		Calacata	Celeste	Crema
	Commercial Interior Floor	✓		
	Commercial Wall Interior & Exterior	✓	interior only	interior only
	Residential Bathroom Floor	✓	✓	✓
	Residential Interior Floor	✓	✓	✓
	Residential Wall Interior & Exterior	✓	interior only	interior only
	Shower Floor	✓		
	Shower Wall	✓		✓
	Steam Showers	wall only		

Material Data		Calacata	Celeste	Crema
<b>MEDIUM</b> 	Color Variation		✓	✓
<b>HIGH</b> 	Color Variation	✓		
Sealing				
	Must be sealed for use in areas that experience frequent wet conditions	✓	✓	✓
Cleaning and Maintenance				
	Protect from harsh abrasive cleaners and tools <i>Recommended: Oceanscare or Dry Treat products</i>			

**Notes:**

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. *The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.*

