



| | |
|--|----------------|
| Material | Stone |
| Finish | Honed |
| Thickness | 3/8" |
| Cut and Fill Size | 13" x 13 3/16" |
| Square Feet/Piece | 1.1901 |
| Mounting | Mesh |
| Available Colors | |
| Ash (Ash Gray, Calacata, Flannel) | |
| Calacata (Calacata) | |
| Linen (Ash Gray, Calacata, French Linen) | |

| Usage | | Ash | Calacata | Linen |
|-------|--------------------------------------|---------------|-----------|---------------|
| | Commercial Interior Floor | | ✓ | |
| | Commercial Interior & Exterior Wall | interior only | ✓ | interior only |
| | Residential Bathroom Floor | ✓ | ✓ | ✓ |
| | Residential Interior Floor | ✓ | ✓ | ✓ |
| | Residential Interior & Exterior Wall | interior only | ✓ | interior only |
| | Shower Floor | | ✓ | |
| | Shower Wall | | ✓ | |
| | Steam Showers | | wall only | |

| Material Data | | Ash | Calacata | Linen |
|---------------------------------|--|-----|----------|-------|
| | Color Variation | ✓ | | ✓ |
| | Color Variation | | ✓ | |
| Sealing | | | | |
| | Must be sealed for use in areas that experience frequent wet conditions | ✓ | ✓ | ✓ |
| Cleaning and Maintenance | | | | |
| | Protect from harsh abrasive cleaners and tools <i>Recommended: Oecare or Dry Treat products</i> | | | |

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. *The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.*

