



<b>Material</b>	Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	11 1/4" x 9 1/8"
<b>Square Feet/Piece</b>	0.7092
<b>Mounting</b>	Mesh
<b>Available Colors</b>	
Ash (Ash, Calacata, Flannel)	
Calacata (Calacata)	

Usage		Ash	Calacata
	Commercial Interior Floor		✓
	Commercial Interior & Exterior Wall	interior only	✓
	Residential Bathroom Floor	✓	✓
	Residential Interior Floor	✓	✓
	Residential Interior & Exterior Wall	interior only	✓
	Shower Floor		✓
	Shower Wall		✓
	Steam Showers		wall only

Material Data		Ash	Calacata
	Color Variation	✓	
	Color Variation		✓
<b>Sealing</b>			
	Must be sealed for use in areas that experience frequent wet conditions	✓	✓
<b>Cleaning and Maintenance</b>			
	Protect from harsh abrasive cleaners and tools Recommended: Oceanscare or Dry Treat products		

**Notes:**

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. *The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.*

