



<b>Material</b>	Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	10" x 10"
<b>Square Feet/Piece</b>	0.7050
<b>Mounting</b>	Mesh
<b>Available Colors</b>	Calacata

Usage	
	Commercial Interior Floor
	Commercial Wall Interior & Exterior
	Residential Bathroom Floor
	Residential Interior Floor
	Residential Wall Interior & Exterior
	Shower Floor
	Shower Wall
	Steam Shower Wall

Material Data	
	Color Variation
Sealing	
	Must be sealed for use in areas that experience frequent wet conditions
Cleaning and Maintenance	
	Protect from harsh abrasive cleaners and tools <i>Recommended:</i> Oceanscare or Dry Treat products

**Notes:**

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. *The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.*

