









Material	Stone Mosaic
Finish	Brushed
Thickness	3/8"
Cut and Fill Size	13 5/8" x 6 3/4"
Square Feet/Piece	0.6400
Mounting	Mesh
Available Colors	Café Sage

Usage	
	Commercial Interior & Exterior Wall
	Commercial Interior Floor
	Residential Bathroom Floor
	Residential Interior & Exterior Wall
	Residential Interior Floor
	Shower Floor
	Shower Wall
	Steam Shower

Material Data



Color Variation

Sealing



Sealing required prior to grouting
*epoxy grout for shower floors

Cleaning and Maintenance



Protect from harsh abrasive cleaners and tools
Recommended: Oceanscare or Dry Treat products

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. *The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.*

