



<b>Material</b>	Decorative Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	6 7/8" x 8 3/8"
<b>Square Feet/Piece</b>	0.4202
<b>Mounting</b>	Mesh
<b>Available Colors</b> Calacata	

Usage	
	Commercial Interior & Exterior Floor & Wall
	Pool & Spa
	Residential Bathroom Floor
	Residential Interior & Exterior Floor
	Residential Interior & Exterior Wall
	Shower Wall
	Shower Floor
	Steam Showers

Material Data	
	Color Variation
Sealing	
	Must be sealed for use in areas that experience frequent wet conditions
Cleaning and Maintenance	
	Protect from harsh abrasive cleaners and tools Recommended: Oceanscare or Dry Treat products for all natural stone

#### Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- If used for shower floors, must include waterproof membrane on substrate and 12 inches up adjacent walls prior to tile installation.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiqued stones", and light colored marbles
- May be characterized by dry seams, pits, fossils, and glass veins (honed stones are often filled at the factory)

