


## SHIFT Chevron Mosaic



Material	Stone			
Finish	Textured			
Thickness	3/8"			
Cut and Fill Size	7-3/5" x 8-1/5"			
Square Feet/Piece	0.4363			
Mounting	Mesh			
Available Colors  Charcoal  Cream  Grey  Moss  White				

Usage	
	Commercial Interior Floor
	Commercial Exterior Wall
	Commercial Interior Wall
	Residential Interior Floor
	Residential Exterior Wall
	Residential Interior Wall
	Shower Wall

Material	Data	Charcoal	Cream	Grey	Moss	White
MEDIUM	Color Variation		<b>✓</b>	<b>✓</b>		<b>✓</b>
HIGH	Color Variation	<b>✓</b>			<b>~</b>	

Sealing	
	Sealing is required prior to grouting

Cleaning and Maintenance			
(C)	Protect from harsh abrasive cleaners and tools		

## Notes:

- We recommend sealing all natural stone products with a penetrating sealer
  and sealing all porous non-polished stone (limestone, tumbled marble, etc.)
  prior to grouting. is prevents grout from staining or affecting the color of the
  stone. Stone is a natural product, and care should be taken to protect it from
  harsh abrasive cleaners and abrasive cleaning tools.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiquated stones", and light colored marbles.
- Likely identified with dry seams, pits, fossils and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

