


Accent Bleu Candy Dot Mosaic

DATE REVISED: APRIL 2024

WALKER
ZANGER®



MATERIAL	Natural Stone
FINISH	Polished
THICKNESS	3/8"
SHEET SIZE	11" x 11"
COVERAGE SQFT/PIECE	0.846 SqFt
MOUNTING	Mesh
AVAILABLE COLORS	
Thassos/Blue Celeste/ Azul Macaubा	

RECOMMENDED USAGES

- | | |
|--|-------------------------------|
| | Commercial
Interior Wall |
| | Residential
Interior Wall |
| | Fireplace
Surround |
| | Shower Floor* |
| | Commercial
Interior Floor |
| | Residential
Interior Floor |
| | Shower Wall |

MATERIAL DATA





MAINTENANCE

- | | |
|--|--|
| | Sealing is required prior to grouting |
| | Clean with a damp cloth and
a gentle, non-acidic soap |

ADDITIONAL NOTES

For installation on shower floors, please refer to TCNA guidelines and consult with your installer for proper waterproofing and sealing requirements. Accent Bleu Candy Dot mosaic tiles feature natural stone products. We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools. White thin-set or mortar is required for the following: light limestone, tumbled stones, "antiquated stones" and light-colored marbles. It is possible that dry seams, pits, fossils, and glass veins are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling the voids may be a necessary maintenance procedure. For further questions/information about additional usages, please consult with your installer.

Accent Bleu
Candy Dot Mosaic
DATE REVISED: APRIL 2024



WALKER ZANGER™