



Material	Stone
Finish	Honed
Thickness	3/8"
Cut and Fill Size	10-1/4" x 10-1/8"
Square Feet/Piece	0.7194
Mounting	Mesh
Available Colors Calacata Paloma/Gascogne Blue	

Usage	
	Commercial Exterior Floor
	Commercial Interior Floor
	Commercial Exterior Wall
	Commercial Interior Wall
	Residential Exterior Floor
	Residential Interior Floor
	Residential Exterior Wall
	Residential Interior Wall
	Shower Wall

Material Data		Calacata	Paloma/ Gascogne Blue
	V1 Color Variation		✓
	V4 Color Variation	✓	
Sealing			
	Sealing is required prior to grouting		
Cleaning and Maintenance			
	Protect from harsh abrasive cleaners and tools		

Notes:

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- If used for shower floors, must include waterproof membrane on substrate and 12 inches up adjacent walls prior to installation.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiquated stones", and light-colored marbles.
- Likely identified with dry seam, pits, fossils, and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

