



<b>Material</b>	Stone
<b>Finish</b>	Honed
<b>Thickness</b>	3/8"
<b>Cut and Fill Size</b>	18" x 2-11/16"
<b>Square Feet/Piece</b>	0.3750
<b>Mounting</b>	Loose
<b>Available Colors</b>	
Calacata	
Steel Grey	

Usage	
	Commercial Exterior Floor
	Commercial Interior Floor
	Commercial Exterior Wall
	Commercial Interior Wall
	Residential Exterior Floor
	Residential Interior Floor
	Residential Exterior Wall
	Residential Interior Wall
	Shower Wall

Material Data	Calacata	Steel Grey
<b>MEDIUM</b>  V3 Color Variation		✓
<b>HIGH</b>  V4 Color Variation	✓	
Sealing		
	Sealing is required prior to grouting	
	Grout with white thinset ( <b>Calacata only</b> )	
Cleaning and Maintenance		
	Protect from harsh abrasive cleaners and tools	

**Notes:**

- We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools.
- If used for shower floors, must include waterproof membrane on substrate and 12 inches up adjacent walls prior to installation.
- White thin-set or mortar is required: light limestones, tumbled stones, "antiquated stones", and light-colored marbles.
- Likely identified with dry seam, pits, fossils, and glass veins that are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling these voids may be a necessary maintenance procedure.

