
## Studio Moderne<sup>™</sup> Stone Parliament

DATE REVISED: MAY 2023

## WALKER<sup>™</sup> ZANGER



MATERIAL	Natural Stone
FINISH	Honed
THICKNESS	3/8″
SHEET SIZE	18" x 2-11/16"
COVERAGE SQFT/PIECE	0.3750 SqFt
MOUNTING	Loose

# AVAILABLE COLORS Calacatta S



#### RECOMMENDED USAGES



Commercial Exterior Wall

Commercial

Residential

Residential

**Exterior Floor** 

Shower Wall

Exterior Wall

**Exterior Floor** 



Commercial Interior Wall



Commercial Interior Floor



Residential Interior Wall



Residential Interior Floor



Shower Floor\*

#### MATERIAL DATA



V3 Color Variation (STEEL GREY ONLY)



V4 Color Variation (CALACATTA ONLY)

#### MAINTENANCE



Sealing is required prior to grouting



Grout with white thin-set (CALACATTA ONLY)



Clean with a damp cloth and a gentle, non-acidic soap

#### ADDITIONAL NOTES

For installation on shower floors, please refer to TCNA guidelines and consult with your installer for proper waterproofing and sealing requirements. Parliament Calacatta and Steel Grey feature natural stone products. We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools. White thin-set or mortar is required for the following: light limestone, tumbled stones, "antiquated stones" and light-colored marbles. It is possible that dry seams, pits, fossils, and glass veins are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling the voids may be a necessary maintenance procedure. For further questions/information about additional usages, please consult with your installer.

### Studio Moderne™ Stone Parliament

DATE REVISED: MAY 2023

