# OPUS ANTICATO<sup>™</sup>

WALKER ZANGER\*



## RECOMMENDED USAGE







Residential Exterior Wall



Residential Interior Floor



tial Commercial



Commercial Exterior Wall



Commercial Interior Floor



Shower Floor\*



Shower W

# CALACATTA BAR LINER

20ANCALBL 5/8" x 12"



## CALACATTA CORNICE MOLDING

20ANCALCM 1-1/4" x 12"



# CALACATTA RAIL MOLDING

20ANCALRM 2" x 12"

# V4 COLOR VARIATION

## RECOMMENDED USAGE



Residential Interior Wall



Residential Exterior Wall



Residential Interior Floor



Commercial Interior Wall



Commercial Exterior Wall



Commercial Interior Floor




Shower Floor\*




Shower Wall

#### DIAMANTE




SIZE	THICKNESS	SF/PIECE	MATERIAL	FINISH
9-1/2" × 11"	3/8"	0.73	Natural Stone	High Honed

## OLD WORLD FIELD




SIZE	THICKNESS	SF/PIECE	MATERIAL	FINISH
12" × 12"	3/8"	1.00	Natural Stone	High Honed

### ONDA



SIZE	THICKNESS	SF/PIECE	MATERIAL	FINISH
14" × 16"	3/8"	1.56	Natural Stone	High Honed



CALACATTA GOLD DIAMANTE
20ANCGODIA



CALACATTA OLD WORLD FIELD

20ANCALOWF



CALACATTA ONDA PATTERN 20ANCALOP1416

Opus Anticato" Old World Field is not recommended for shower floor application. For installation on shower floors, please refer to TCNA guidelines and consult with your installer for proper waterproofing and sealing requirements. We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools. For further questions/information about usages, please consult with your installer.

