


Rue Pierre Dot

DATE REVISED: NOVEMBER 2023

WALKER ZANGER™



MATERIAL	Natural Stone
FINISH	Antiqued
THICKNESS	3/8"
SHEET SIZE	3" x 3"
COVERAGE SQFT/PIECE	0.1276 SqFt
MOUNTING	Loose

AVAILABLE COLORS

	
Gris	Noir

RECOMMENDED USAGES



Commercial
Exterior Wall



Commercial
Interior Wall



Residential
Exterior Wall



Residential
Interior Wall



Residential
Interior Floor



Fireplace
Surround



Shower Wall



Shower Floor*


MATERIAL DATA

HIGH
 V4 Color Variation

 Frost Resistant

MAINTENANCE

 Sealing is required prior to grouting

 Clean with a damp cloth and a gentle, non-acidic soap

ADDITIONAL NOTES

For installation on shower floors, please refer to TCNA guidelines and consult with your installer for proper waterproofing and sealing requirements. Rue Pierre Dot tiles feature natural stone products. We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools. White thin-set or mortar is required for the following: light limestone, tumbled stones, "antiquated stones" and light-colored marbles. It is possible that dry seams, pits, fossils, and glass veins are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling the voids may be a necessary maintenance procedure. For further questions/information about additional usages, please consult with your installer.

Rue Pierre
Dot

DATE REVISED: NOVEMBER 2023

