


Tatami

6" x 24" Field

DATE REVISED: DECEMBER 2023

WALKER
ZANGER™



MATERIAL	Natural Stone
FINISH	Textured
THICKNESS	3/8"
SHEET SIZE	6" x 24"
COVERAGE SQFT/PIECE	1.00 SqFt
MOUNTING	Loose

AVAILABLE COLORS



Bone

Pearl

RECOMMENDED USAGES



Commercial Exterior Wall



Commercial Interior Wall



Commercial Exterior Floor



Commercial Interior Floor



Residential Exterior Wall



Residential Interior Wall



Residential Exterior Floor



Residential Interior Floor



Fireplace Surround



Shower Wall



Shower Floor*



Steam Shower Wall

MATERIAL DATA



V2 Color Variation

MAINTENANCE



Sealing is required



Clean with a damp cloth and a gentle, non-acidic soap

ADDITIONAL NOTES

For installation on shower floors, please refer to TCNA guidelines and consult with your installer for proper waterproofing and sealing requirements. Tatami 6"x24" Field tiles feature natural stone products. We recommend sealing all natural stone products with a penetrating sealer and sealing all porous non-polished stone (limestone, tumbled marble, etc.) prior to grouting. This prevents grout from staining or affecting the color of the stone. Stone is a natural product, and care should be taken to protect it from harsh abrasive cleaners and abrasive cleaning tools. White thin-set or mortar is required for the following: light limestone, tumbled stones, "antiquated stones" and light-colored marbles. It is possible that dry seams, pits, fossils, and glass veins are often filled at the factory. The fill may perhaps leak through the voids. In this case, refilling the voids may be a necessary maintenance procedure. For further questions/information about additional usages, please consult with your installer.

Tatami
6" x 24" Field

DATE REVISED: DECEMBER 2023

