

ANTICA TERRA

WALKER ZANGER™

WALKERZANGER.COM



LIMESTONE | ZELLIGE GLAZED CERAMIC | UNGLAZED TERRACOTTA


FLOOR & WALL TILE

Latte | 1ATEPALLATMOS



WAL ATLA PALERMO

Berber | 1ATEPALBERMOS



WAL ATBE PALERMO

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
12" x 12" Palermo	11.73" x 11.73"	10mm	Mixed Finishes

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

Ready Ship



LIMESTONE | ZELLIGE GLAZED CERAMIC | UNGLAZED TERRACOTTA

FLOOR & WALL TILE

Latte | 1ATETANLATMOS



WAL ATLA TANGIERS

Berber | 1ATETANBERMOS



WAL ATBE TANGIERS

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
12" x 12" Tangiers	11.85" x 11.85"	10mm	Mixed Finishes

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

Ready Ship

ANTICA TERRA

LIMESTONE | ZELLIGE

FLOOR & WALL TILE

Ready Ship

Latte | 1ATECHELATMOS



WAL ATLA CHECK

Gris | 1ATECHEGRIMOS



WAL ATGR CHECK

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
2" x 2" Check	11.77" x 11.77"	10mm	Mixed Finishes

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A





ANTICA TERRA

LIMESTONE | ZELLIGE | UNGLAZED TERRACOTTA

FLOOR & WALL TILE

Ready Ship

Latte | 1ATEPICLATMOS



WAL ATLA PICK13

Berber | 1ATEPICBERMOS



WAL ATBE PICK13

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
1" x 3" Picket	11.54" x 12.28"	10mm	Mixed Finishes

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ZELLIGE

GLOSS WALL TILE

Blanco | 2ATEHABBLDEMOS



WAL ATBL HABIBAG

Desert | 2ATEHABDEFOMOS



WAL ATDE HABIBAG

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
11″ x 11″ Habiba	10.55″ x 10.55″	16mm	Gloss

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

Ready Ship



LIMESTONE

FLOOR & WALL TILE

Luberon | 2ATELUBTUMMOS22



WAL ATLU MOS22T

Gris | 2ATEGRITUMMOS22



WAL ATGR MOS22T

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
2″ x 2″ Mosaic	12″ x 12″	10mm	Tumbled

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

Ready Ship

ANTICA TERRA

UNGLAZED TERRACOTTA

FLOOR & WALL TILE

Stock and Ready Ship

Blond Cotto | 1ATEBLOCOT29



WAL ATBD 29

Rojo Cotto | 1ATEROJCOT29



WAL ATRO 29

FIELD TILE	ACTUAL	THICKNESS	FINISH
2" x 9"	2.007" x 8.937"	16mm	Natural

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ANTICA TERRA

LIMESTONE

FLOOR & WALL TILE

Ready Ship

Luberon | 2ATELUBHERMOS14



WAL ATGR 14HERRT

Gris | 2ATEGRIHERMOS14



WAL ATLU 14HERRT

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
1" x 4" Herringbone	8.582" x 11.338"	10mm	Tumbled

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

Luberon | 2ATE LUBHER MOS110



WAL ATLU 210HERR

Ready Ship

MOSAIC TILE	ACTUAL	THICKNESS	FINISH
1.5" x 10" Herringbone	9.842" x 11.062"	10mm	Natural

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

ANTICA TERRA

UNGLAZED TERRACOTTA

FLOOR & WALL TILE

Ready Ship

Blond Cotto | 1ATEBLOCOT48



WAL ATBD 48

Rojo Cotto | 1ATEROJCOT48



WAL ATRO 48

FIELD TILE	ACTUAL	THICKNESS	FINISH
4" x 8"	3.937" x 7.677"	16mm	Natural

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ANTICA TERRA



4" x 8" x 16mm

ANTICA TERRA

LIMESTONE

FLOOR & WALL TILE

Stock

Luberon | 2ATELUBTUM312



WAL ATLU 312T

Gris | 2ATEGRITUM312



WAL ATGR 312T

FIELD TILE	ACTUAL	THICKNESS	FINISH
3" x 12"	2.99" x 12.01"	15mm	Tumbled

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ANTICA TERRA

3" x 12" x 15mm Tumbled

ANTICA TERRA

LIMESTONE

FLOOR & WALL TILE

Ready Ship

Luberon | 2ATELUBPICMOS410



WAL ATLU PICK410

FIELD TILE	ACTUAL	THICKNESS	FINISH
4" x 10" Picket	3.937" x 9.842"	12mm	Natural

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



4" x 10" x 12mm Natural



16" x 24" x 15mm Tumbled

LIMESTONE

FLOOR & WALL TILE

Luberon | 2ATELUBTUM1624



WAL ATLU 1624T

FIELD TILE	ACTUAL	THICKNESS	FINISH
16″ x 24″	15.98″ x 24.02″	15mm	Tumbled

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A

ANTICA TERRA

GLAZED CERAMIC

Stock and Ready Ship

FLOOR & WALL TILE

**If used for flooring, expect wear and tear on the tiles, which may include glaze wearing off the edges, or chipping off the surface, as well as cracks, or complete failure of occasional tiles.

Blanco | Gloss
1ATEALHBLAGL



WAL ATBL ALHAMBRAG

Desert | Gloss
1ATEALHDESGL



WAL ATDE ALHAMBRAG

Cotto | Natural
1ATEALHCOTNA



WAL ATCO ALHAMBRAN

Verde | Gloss
1ATEALHVERGL



WAL ATVE ALHAMBRAG

Café | Gloss
1ATEALHCAFGL



WAL ATCA ALHAMBRAG

FIELD TILE	ACTUAL	THICKNESS	FINISH
4.375" x 4.375" Star	4.375" x 4.375"	16mm	Natural/Glossy
3" x 3" Cross	3" x 3"	16mm	Natural/Glossy

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A




ANTICA TERRA

4.375" x 4.375" x 16mm

3" x 3" x 16mm



ANTICA TERRA



2" x 6" x 16mm

ANTICA TERRA

GLAZED CERAMIC

Stock and Ready Ship

FLOOR & WALL TILE

**If used for flooring, expect wear and tear on the tiles, which may include glaze wearing off the edges, or chipping off the surface, as well as cracks, or complete failure of occasional tiles.

Blanco | Gloss
1ATESOUBLAGL



WAL ATBL SOUKG

Desert | Gloss
1ATESOUDESGL



WAL ATDE SOUKG

Cotto | Matte
1ATESOUCOTNA



WAL ATCO SOUKN

Verde | Gloss
1ATESOUVERGL



WAL ATVE SOUKG

Café | Gloss
1ATESOUCAFGL



WAL ATCA SOUKG

FIELD TILE	ACTUAL	THICKNESS	FINISH
2" x 6" Souk	1.456" x 5.905"	16mm	Gloss/Matte

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ANTICA TERRA

4" x 4" x 12mm Gloss

ANTICA TERRA

ZELLIGE

WALL TILE

Stock and Ready Ship

Blanco
1ATEBLAZLGGL44



WAL ATBL ZLG44G

Desert
1ATEDESZLGGL44



WAL ATDE ZLG44G

Fog
1ATEFOGZLGGL44



WAL ATFO ZLG44G

Aquamarine
1ATEAQUZLGGL44



WAL ATAQ ZLG44G

FIELD TILE	ACTUAL	THICKNESS	FINISH
4” x 4” Zellige	3.94” x 3.94”	12mm	Gloss

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



ANTICA TERRA

2" x 6" x 12mm Gloss

ANTICA TERRA

GLAZED CERAMIC

WALL TILE

Stock and Ready Ship

Blanco
1ATEBLAGL26



WAL ATBL 26G

Desert
1ATEDESGL26



WAL ATDE 26G

Fog
1ATEFOGGL26



WAL ATFO 26G

Aquamarine
1ATEAQUGL26



WAL ATAQ 26G

FIELD TILE	ACTUAL	THICKNESS	FINISH
2" x 6"	1.7716" x 5.7086"	12mm	Gloss

SUBSTANTIAL VARIATION	DCOF	WATER ABSORPTION
N/A	N/A	N/A



PRODUCT CHARACTERISTICS	MIXED FINISHES
Breaking Strength (ASTM C648 or ISO 10545-4)	N/A
Chemical Resistance (ASTM C650 or ISO 10545-13)	N/A
DCOF	N/A
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Not Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	N/A
Certifications	N/A
Shade Variation Code	N/A

CARE AND MAINTENANCE FOR ANTICA TERRA SERIES TILES

GENERAL CLEANING AND MAINTENANCE

Regular care and maintenance will help keep tiled surfaces looking their best and extend their longevity. Routine cleaning should be performed using warm water and a light-duty, pH-neutral cleaner or other non-abrasive cleaning solutions recommended for tile surfaces.

ROUTINE MAINTENANCE

- Sweep or vacuum regularly to remove loose dirt, dust, and debris before they accumulate on the surface.
- Wipe surfaces with a slightly damp cloth and clean water as needed.
- Clean spills as quickly as possible to help prevent staining and surface damage.

CLEANING PROCEDURES

When more thorough cleaning is required:

- Use hot water mixed with a weak dilution of close-to-neutral pH detergent additive. More is not always better; higher concentrations of detergent in the cleaning solution will only make it more difficult to rinse.
- Allow the cleaning solution sufficient dwell time to act on the soil load, following product label instructions.
- Gently scrub using a non-abrasive white scrub pad, soft-bristle brush, or soft cloth.
- Rinse thoroughly with clean water to remove any residue.
- Dry the surface with a clean mop, microfiber towel, or soft cloth.

PRODUCTS AND METHODS TO AVOID

Do not use:

- Acid-based cleaners.
- Alkaline cleaners.
- Solvent-based cleaners.
- Abrasive cleaning tools or harsh chemicals that may damage the tile surface, grout, or protective sealers.

SEALING AND PROTECTION

Patina Development
Over time, terracotta tiles can develop a patina. Clients should anticipate that the cotto may show wear patterns that are distinct from other areas of the floor. This is a normal and desirable characteristic of this material.

Protective sealing is strongly recommended to help resist staining and moisture intrusion. Reapplication frequency will depend on product type, traffic levels, wear patterns, and moisture exposure. Always follow the sealant manufacturer's instructions and recommendations.

PROFESSIONAL MAINTENANCE

For stubborn stains, extensive soiling, or long-term maintenance needs, consultation with a professional cleaning, restoration, or stone-care specialist is recommended.

ARTIVO SURFACES™

VIRGINIATILE WALKER ZANGER GALLEHERDUFFY

February 9, 2026

Subject: Lead-Free Compliance Confirmation – Zellige Ceramic Tile

To Whom It May Concern,

This letter confirms that Antica Terra Zellige Tile products comply with applicable U.S. federal regulations regarding lead content and may be represented as Lead-Free in accordance with established regulatory standards.

Testing was conducted by the International Product Assurance Laboratory (IPAL), an ISO/IEC 17025-accredited testing laboratory, using applicable ISO and ASTM testing methodologies and X-Ray Fluorescence (XRF) analysis to determine lead content in ceramic and glazed products. All testing procedures were performed in accordance with guidance issued by the U.S. Consumer Product Safety Commission (CPSC).

Under current CPSC regulations, consumer products may contain up to 100 parts per million (ppm), or 0.01%, total lead in accessible components. Additionally, paints and similar surface coatings are considered lead-free when lead content does not exceed 90 ppm (0.009%).

Laboratory testing of our ceramic tile, documented in IPAL Test Report No. 0734-25, confirmed a lead content of 67 ppm. This result is below both the 90 ppm surface coating threshold and the 100 ppm total lead content limit. While the term “lead-free” does not imply the complete absence of lead, it signifies compliance with applicable regulatory limits and recognizes that trace environmental levels may be present.

Based on these test results and current regulatory guidance, our ceramic tile products meet all applicable lead-content requirements and may be designated as Lead-Free.
Should you require additional information or supporting documentation, please do not hesitate to contact us.

40250 Schoolcraft Road
Plymouth, MI 40250

734.762.2400
Artivosurfaces.com